



Fujitsu fi-6400 A3 Document Scanners FJ3077



The fi-6400 is the perfect scanning solution for small and medium sized companies who are looking to introduce a centralised document capture solution. Larger corporations seeking added flexibility from their scanning infrastructure could utilise the affordable fi-6400 for applications where decreasing scan requirements are needed across multiple locations, when there is a need for a higher throughput scanner to cover peak times or simply as a back-up system.

The fi-6400 minimises operator interference through automated functionality to provide uninterrupted performance when processing large batches of documents. The fi-6400 can scan at speeds of 100 pages per minute (ppm) or when double sided 200 images per minute (ipm) at 300 dpi in A4 landscape mode (85ppm/170ipm in A4 portrait mode). When higher resolutions are needed operators can select up to 600 optical dpi.

Main features: 100ppm (200ipm), 500p ADF, A3, True Duplex, USB2, 1 year warranty NBD OS covering up to 40,000 pages/day.

Fujitsu fi-6400

A3 Document Scanners

fi-6400 Specifications	
ADF (Doc. Feeder)	Yes
ADF Scan Area - Max.	297x420 mm
ADF Scan Area - Min.	52x74 mm
Duplex or Simplex	True Duplex
ADF Speed (ppm)	100
ADF Capacity (pages)	500
ADF Speed Duplex (ipm)	200
ADF Paper Path	U
Paper Weight	20 to 209 gsm (A4) or 41 to 209 gsm for other sizes
Duty Cycle	★★★★★
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CCD x 2
Interface	USB2
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, TIFF, JPEG, BMP
Supported OS	WINDOWS 7, Win 8.1, Win 10. Server 2008, 2012, 2016
Software Standards	TWAIN, ISIS (included)
Imaging Features	Automatic colour detection, Automatic page size detection, De-Skew, Automatic orientation, Upper lower separation, Multi-image, Blank page skip, Error diffusion, Dither, Dropout colour (R, G, B, None, White, Specified, Saturation), Image emphasis, Simplif
In the Box	PaperStream IP Driver (TWAIN & ISIS™), 2D Barcode for PaperStream, Software Operation Panel, Error Recovery Guide, PaperStream Capture, Scanner Central Admin tools
Electrical	Input: 100-240 VAC, 50/60 Hz. Power consumption:
Light Source	LED
Dimensions	460x430x310 mm
PC Configuration	Minimum: 1GB RAM, USB2. Recommended: 4GB RAM, USB2
Weight	40
Operating Environment	15°C to 35°C, 20-80%RH
Warranty	12 months parts & labour warranty