![Fujitsu logo]

The Fujitsu ScanSnap S1100i Portable Scanner is easily one of the smallest mobile A4 scanners on the market. This scanner can scan plastic cards and has Continuous Document Feeding (CDF Function) which allows the user to insert pages one after another without any extra button pressing by detecting when a sheet enters and exits the S1100i. Scanning a two-sided document using the CDF Function is easy, insert the page face up and press the Scan button, the S1100i proceeds to scan the front side and the page exits facing front side down, simply reinsert the page without pressing the Scan button. The page is then scanned, press the Scan button to end the scanning process and create a PDF image file. The Fujitsu ScanSnap S1100i delivers a snappy 7.5 seconds/page (approximately 8 ppm) scanning speed for color A4 documents at resolutions up to 300 dpi. Link ScanSnap to iPad & iPhone devices too.

Main features: A4, USB2, scans to PDF file (not Twain), for Windows & Mac, 1 year warranty RTB. ScanSnap Manager v5.1, ScanSnap Organiser v4.1, CardMinder v4.1, ABBYY FineReader for ScanSnap 4.1(Mac & Win), Scan to Microsoft Sharepoint3.3, ScanSnap Manager(Mac v3.1), Cardiris 3.6 for ScanSnap(Mac)

Fujitsu ScanSnap S1100i
Portable Scanners

ScanSnap S1100i Specifications	
ADF (Doc. Feeder)	Yes
ADF Scan Area - Max.	216x360 mm
ADF Scan Area - Min.	25.4x25.4 mm
Duplex or Simplex	Simplex
ADF Capacity (pages)	1
ADF Paper Path	Straight & U
Paper Weight	52 to 209 gsm
Duty Cycle	★☆☆☆☆
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CIS
Interface	USB2
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, JPEG
Supported OS	WINDOWS XP (32), VISTA, Win 7, Win 8 (32/64), Mac OS X 10.4-10.10
Software Standards	Direct scan to PDF (not Twain or ISIS). If you require a scanner with Twain or ISIS support see the fi-6110 or fi-6130Z.
Imaging Features	Deskewing, auto-crop, blank page removal.
In the Box	ScanSnap Manager, ScanSnap Organizer, CardMinder, ABBYY FineReader, Evernote, SharePoint
Electrical	Power consumption:
Light Source	LED
Dimensions	273x48x34 mm
PC Configuration	Minimum: 1GB RAM, USB1. Recommended: 2GB RAM, 2 x USB2 ports
Weight	1
Operating Environment	5°C to 35°C, 20-80%RH
Warranty	12 months parts & labour warranty