



Fujitsu fi-7160 A4 Document Scanners FJ3011



The Fujitsu fi-7160 is a desktop A4 document scanner, featuring an 80 page ADF. It replaces the popular Fujitsu fi-6130Z scanner. The Fujitsu fi-7160 scans colour A4 documents at a speed of 60 ppm / 120 ipm in duplex mode. The scanner is capable of setting up to 80 pages, in the large volume hopper which allows quick digitising of large volumes of documents. The scanner supports USB3.0 for high speed data transfer between scanner and the computer. The Fujitsu fi-7160 has the ability to scan mixed documents, small cards or extra long documents. It includes PaperStream IP which features advanced image processing at Twain/ISIS driver level, and the PaperStream Capture application. The LCD is equipped on the operational panel to display the operational settings for scanning documents, the number of sheets scanned, and error status. It is used to easily check the status of the scanner. The Paper Protection II function reduces the risk of having the documents damaged by stopping the scan when the scanner detects paper jam sound. The scanner is equipped with "Skew Reducer" to ensure straight paper feeding even for mix batch of small or thin papers which prevents the occurrence of missing the edge of the scanned image data.

Main Features: 60ppm (120ipm), 80p ADF, A4, True Duplex, USB3. 1 year warranty RTB.

Fujitsu fi-7160

A4 Document Scanners

fi-7160 Specifications	
ADF (Doc. Feeder)	Yes
ADF Scan Area - Max.	210x5461 mm
ADF Scan Area - Min.	51x54 mm
Duplex or Simplex	True Duplex
ADF Speed (ppm)	60
ADF Capacity (pages)	80
ADF Speed Duplex (ipm)	120
ADF Paper Path	Straight
Paper Weight	27 to 413 gsm for A4 (126 to 209 gsm for A8 size)
Duty Cycle	★★★★★
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CCD x 2
Interface	USB3.0/2.0
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, TIFF, JPEG, BMP
Supported OS	WINDOWS 7, Win 8.1, Win 10. Server 2008, 2012, 2016
Software Standards	TWAIN, ISIS drivers
Imaging Features	Deskewing, sharpening, auto-crop, blank page removal, page separation, dynamic thresholding, noise removal
In the Box	PaperStream Capture, ScanSnap Manager, FineReader OCR for ScanSnap, Central Admin Agent, USB Cable
Electrical	Input: 100-240 VAC, 50/60 Hz. Power consumption:
Light Source	LED
Dimensions	300x170x163 mm
PC Configuration	Minimum: 2GB RAM, USB2. Recommended: 4GB RAM
Weight	6
Operating Environment	5°C to 35°C, 20-80%RH
Warranty	12 months parts & labour warranty